


82 Series Fittings

Use with 801, 804, 821, 821FR, 831 and 836 hoses.

Pipe

30182 Male NPTF Pipe - Rigid Straight



Note: "B" - Brass Fitting.

Note: "C" - Stainless Steel Fitting.

Part Number	Thread		Hose		A		H	B	
	inch		inch		inch	mm	inch	inch	mm
30182-2-4	1/8x27	-2	1/4	-4	1.39	35	7/16	0.63	16
30182-2-4B	1/8x27	-2	1/4	-4	1.39	35	7/16	0.63	16
30182-2-4C	1/8x27	-2	1/4	-4	1.39	35	7/16	0.63	16
30182-2-6+	1/8x27	-2	3/8	-6	1.53	39	1/2	0.63	16
30182-2-6B+	1/8x27	-2	3/8	-6	1.53	39	1/2	0.63	16
30182-2-6C+	1/8x27	-2	3/8	-6	1.53	39	1/2	0.63	16
30182-4-4	1/4x18	-4	1/4	-4	1.57	40	9/16	0.82	21
30182-4-4B	1/4x18	-4	1/4	-4	1.57	40	9/16	0.82	21
30182-4-4C	1/4x18	-4	1/4	-4	1.57	40	9/16	0.82	21
30182-4-6	1/4x18	-4	3/8	-6	1.78	45	9/16	0.88	22
30182-4-6B	1/4x18	-4	3/8	-6	1.78	45	9/16	0.88	22
30182-4-6C	1/4x18	-4	3/8	-6	1.78	45	9/16	0.88	22
30182-4-8+	1/4x18	-4	1/2	-8	1.93	49	5/8	0.88	22
30182-4-8B+	1/4x18	-4	1/2	-8	1.93	49	5/8	0.88	22
30182-4-8C+	1/4x18	-4	1/2	-8	1.93	49	5/8	0.88	22
30182-6-4+	3/8x18	-6	1/4	-4	1.64	42	11/16	0.88	22
30182-6-4B+	3/8x18	-6	1/4	-4	1.64	42	11/16	0.88	22
30182-6-6	3/8x18	-6	3/8	-6	1.78	45	11/16	0.88	22
30182-6-6B	3/8x18	-6	3/8	-6	1.78	45	11/16	0.88	22
30182-6-6C	3/8x18	-6	3/8	-6	1.78	45	11/16	0.88	22
30182-6-8	3/8x18	-6	1/2	-8	1.93	49	11/16	0.88	22
30182-6-8B	3/8x18	-6	1/2	-8	1.93	49	11/16	0.88	22
30182-8-4+	1/2x14	-8	1/4	-4	1.89	48	7/8	1.13	29
30182-8-6+	1/2x14	-8	3/8	-6	2.03	52	7/8	1.13	29
30182-8-6C	1/2x14	-8	3/8	-6	2.03	52	7/8	1.13	29
30182-8-6B	1/2x14	-8	3/8	-6	2.03	52	7/8	1.13	29
30182-8-8	1/2x14	-8	1/2	-8	2.18	55	7/8	1.13	29
30182-8-8B	1/2x14	-8	1/2	-8	2.18	55	7/8	1.13	29
30182-8-8C	1/2x14	-8	1/2	-8	2.18	55	7/8	1.13	29
30182-8-10	1/2x14	-8	5/8	-10	2.58	66	7/8	1.13	29
30182-8-10B	1/2x14	-8	5/8	-10	2.58	66	7/8	1.13	29
30182-8-12+	1/2x14	-8	3/4	-12	2.58	66	7/8	1.13	29
30182-8-12B	1/2x14	-8	3/4	-12	2.58	66	7/8	1.13	29
30182-12-8B	3/4x14	-12	1/2	-8	2.21	56	1-1/16	1.16	29
30182-12-10+	3/4x14	-12	5/8	-10	2.61	66	1-1/16	1.16	29
30182-12-12	3/4x14	-12	3/4	-12	2.61	66	1-1/16	1.16	29
30182-12-12B	3/4x14	-12	3/4	-12	2.61	66	1-1/16	1.16	29
30182-12-12C	3/4x14	-12	3/4	-12	2.61	66	1-1/16	1.16	29
30182-16-8B+	1x11-1/2	-16	1/2	-8	2.66	68	1-3/8	1.62	41
30182-16-8C+	1x11-1/2	-16	1/2	-8	2.55	65	1-3/8	1.51	38
30182-16-16+	1x11-1/2	-16	1	-16	3.06	78	1-3/8	1.61	41
30182-16-16B	1x11-1/2	-16	1	-16	3.06	78	1-3/8	1.61	41

+ Non-Standard

31382 Male NPTF Pipe - Swivel Straight

Note: This fitting allows minor movement under pressure to relieve stress on hose. It is not to be used for continuous or extreme swiveling.


Note: O-Ring is not compatible with Phosphate Ester Fluids.

Note: Fittings with an "SM" suffix have a metric hex.

Note: "B" - Brass Fitting.


Note: "C" - Stainless Steel Fitting.

Note: "V" - Viton® Seal.



# Part Number	 Thread		 Hose		A		 H	 W	B	
	inch		inch		inch	mm	inch	inch	inch	mm
31382-2-4+	1/8x27	-2	1/4	-4	2.80	71	1/2	5/8	2.05	52
31382-2-6+	1/8x27	-2	3/8	-6	2.96	75	1/2	5/8	2.06	52
31382-4-4	1/4x18	-4	1/4	-4	1.60	41	-----	9/16	0.85	22
31382-4-4B+	1/4x18	-4	1/4	-4	1.60	41	-----	9/16	0.85	22
31382-4-4C+	1/4x18	-4	1/4	-4	1.60	41	-----	9/16	0.85	22
31382-4-6+	1/4x18	-4	3/8	-6	2.70	69	1/2	5/8	1.80	46
31382-6-6	3/8x18	-6	3/8	-6	1.79	45	-----	11/16	0.89	23
31382V-6-6C+	3/8x18	-6	3/8	-6	1.79	45	-----	11/16	0.89	23
31382-8-8	1/2x14	-8	1/2	-8	2.20	56	-----	7/8	1.15	29
31382-8-8C+	1/2x14	-8	1/2	-8	2.20	56	-----	7/8	1.15	29
31382-8-8-SM+	1/2x14	-8	1/2	-8	2.20	56	-----	24mm	1.15	29
31382-8-10+	1/2x14	-8	5/8	-10	3.61	92	3/4	7/8	2.16	55
31382-12-12	3/4x14	-12	3/4	-12	3.70	94	7/8	1-1/4	2.25	57

30282 Female NPTF Pipe - Rigid Straight



Note: "B" - Brass Fitting.

# Part Number	 Thread		 Hose		A		 H	B	
	inch		inch		inch	mm	inch	inch	mm
30282-2-4+	1/8x27	-2	1/4	-4	1.57	40	3/4	0.81	21
30282-2-4B+	1/8x27	-2	1/4	-4	1.57	40	3/4	0.81	21
30282-4-4	1/4x18	-4	1/4	-4	1.56	40	3/4	0.81	21
30282-4-4B	1/4x18	-4	1/4	-4	1.56	40	3/4	0.81	21
30282-4-6+	1/4x18	-4	3/8	-6	1.75	44	3/4	0.85	22
30282-4-6B+	1/4x18	-4	3/8	-6	1.75	44	3/4	0.85	22
30282-6-6B	3/8x18	-6	3/8	-6	1.82	46	7/8	0.92	23
30282-8-8B	1/2x14	-8	1/2	-8	2.16	55	1-1/16	1.11	28
30282-8-10+	1/2x14	-8	5/8	-10	2.56	65	1-1/16	1.11	28
30282-12-10+	3/4x14	12	5/8	-10	2.59	66	1-3/8	1.09	28
30282-12-12+	3/4x14	12	3/4	-12	2.59	66	1-3/8	1.15	29


+ Non-Standard

82 Series Fittings

Pipe / JIC


Use with 801, 804, 821, 821FR, 831 and 836 hoses.

37G82 Female NPSM Pipe Gasket Joint - Swivel - Straight



Part Number	Gasket	Thread		Hose		A		W	B	
		inch		inch		inch	mm	inch	inch	mm
37G82-4-4	07G-4	1/4x18	-4	1/4	-4	1.55	39	11/16	0.79	20
37G82-4-6	07G-4	1/4x18	-4	3/8	-6	1.70	43	11/16	0.80	20
37G82-6-6	07G-6	3/8x18	-6	3/8	-6	1.75	44	7/8	0.85	22
37G82-8-8	07G-8	1/2x14	-8	1/2	-8	2.07	53	1	1.02	26
37G82-8-10	07G-8	1/2x14	-8	5/8	-10	2.47	63	1	1.02	26
37G82-12-12	07G-12	3/4x14	-12	3/4	-12	2.54	65	1-1/4	1.08	27

30382 Male JIC 37° - Rigid Straight



Note: "B" - Brass Fitting.

Note: "C" - Stainless Steel Fitting.

Part Number	Thread			Hose		A		H	B	
	inch			inch		inch	mm	inch	inch	mm
30382-4-4	1/4	7/16x20	-4	1/4	-4	1.56	40	1/2	0.81	21
30382-4-4B+	1/4	7/16x20	-4	1/4	-4	1.56	40	1/2	0.81	21
30382-4-4C+	1/4	7/16x20	-4	1/4	-4	1.56	40	1/2	0.81	21
30382-4-6B+	1/4	7/16x20	-4	3/8	-6	1.71	43	1/2	0.81	21
30382-5-4	5/16	1/2x20	-5	1/4	-4	1.59	40	9/16	0.84	21
30382-5-4B+	5/16	1/2x20	-5	1/4	-4	1.59	40	9/16	0.84	21
30382-6-4+	3/8	9/16x18	-6	1/4	-4	1.64	42	5/8	0.89	23
30382-6-4B+	3/8	9/16x18	-6	1/4	-4	1.64	42	5/8	0.89	23
30382-6-6	3/8	9/16x18	-6	3/8	-6	1.78	45	5/8	0.88	22
30382-6-6B	3/8	9/16x18	-6	3/8	-6	1.78	45	5/8	0.88	22
30382-6-8+	3/8	9/16x18	-6	1/2	-8	1.93	49	5/8	0.88	22
30382-6-8B+	3/8	9/16x18	-6	1/2	-8	1.93	49	5/8	0.88	22
30382-8-8+	1/2	3/4x16	-8	1/2	-8	2.06	52	3/4	1.01	26
30382-8-8B+	1/2	3/4x16	-8	1/2	-8	2.06	52	3/4	1.01	26
30382-8-8C+	1/2	3/4x16	-8	1/2	-8	2.06	52	3/4	1.01	26
30382-8-12C+	1/2	3/4x16	-8	3/4	-12	2.51	64	1-1/8	1.07	27
30382-10-8+	5/8	7/8x14	-10	1/2	-8	2.22	56	7/8	1.17	30
30382-10-10+	5/8	7/8x14	-10	5/8	-10	2.62	67	7/8	1.17	30
30382-10-10B+	5/8	7/8x14	-10	5/8	-10	2.62	67	7/8	1.17	30
30382-12-12+	3/4	1-1/16x12	-12	3/4	-12	2.72	69	1-1/8	1.27	32
30382-12-12B+	3/4	1-1/16x12	-12	3/4	-12	2.72	69	1-1/8	1.27	32
30382-16-16+	1	1-5/16x12	-16	1	-16	3.10	79	1-3/8	1.65	42
30382-16-16B+	1	1-5/16x12	-16	1	-16	3.10	79	1-3/8	1.65	42

+ Non-Standard

82 Series Fittings

JIC


Use with 801, 804, 821, 821FR, 831 and 836 hoses.

30682 Female JIC 37° Swivel

~ These 30682 fittings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations. The -6 and -12 SAE (45°) swivel fittings are shown under part number 30882.

Note: "B" - Brass Fitting.

Note: "C" - Stainless Steel Fitting.



 Part Number										
	Thread			Hose		A		W	B	
	inch			inch		inch	mm	inch	inch	mm
30682-4-4~	1/4	7/16x20	-4	1/4	-4	1.52	39	9/16	0.76	19
30682-4-4B~	1/4	7/16x20	-4	1/4	-4	1.52	39	9/16	0.76	19
30682-4-4C~	1/4	7/16x20	-4	1/4	-4	1.52	39	9/16	0.76	19
30682-4-8B~+	1/4	7/16x20	-4	1/2	-8	1.82	46	9/16	0.76	19
30682-5-4~	5/16	1/2x20	-5	1/4	-4	1.58	40	5/8	0.83	21
30682-5-4B~	5/16	1/2x20	-5	1/4	-4	1.58	40	5/8	0.83	21
30682-5-4C~+	5/16	1/2x20	-5	1/4	-4	1.58	40	5/8	0.83	21
30682-5-6B~+	5/16	1/2x20	-5	3/8	-6	1.72	44	5/8	0.83	21
30682-6-4+	3/8	9/16x18	-6	1/4	-4	1.61	41	11/16	0.86	22
30682-6-4B	3/8	9/16x18	-6	1/4	-4	1.61	41	11/16	0.86	22
30682-6-4C+	3/8	9/16x18	-6	1/4	-4	1.61	41	11/16	0.86	22
30682-6-6	3/8	9/16x18	-6	3/8	-6	1.80	46	11/16	0.85	22
30682-6-6B	3/8	9/16x18	-6	3/8	-6	1.80	46	11/16	0.85	22
30682-6-6C	3/8	9/16x18	-6	3/8	-6	1.80	46	11/16	0.85	22
30682-6-8+	3/8	9/16x18	-6	1/2	-8	1.95	50	11/16	0.85	22
30682-6-8B+	3/8	9/16x18	-6	1/2	-8	1.95	50	11/16	0.85	22
30682-8-6~+	1/2	3/4x16	-8	3/8	-6	1.86	47	7/8	0.96	24
30682-8-6B~	1/2	3/4x16	-8	3/8	-6	1.86	47	7/8	0.96	24
30682-8-6C~+	1/2	3/4x16	-8	3/8	-6	1.86	47	7/8	0.96	24
30682-8-8~	1/2	3/4x16	-8	1/2	-8	2.01	51	7/8	0.96	24
30682-8-8B~	1/2	3/4x16	-8	1/2	-8	2.01	51	7/8	0.96	24
30682-8-8C~	1/2	3/4x16	-8	1/2	-8	2.01	51	7/8	0.96	24
30682-8-10~+	1/2	3/4x16	-8	5/8	-10	2.41	61	7/8	0.96	24
30682-10-8~+	5/8	7/8x14	-10	1/2	-8	2.03	52	1	0.98	25
30682-10-8B~	5/8	7/8x14	-10	1/2	-8	2.03	52	1	0.98	25
30682-10-10~	5/8	7/8x14	-10	5/8	-10	2.43	62	1	0.98	25
30682-10-10B~	5/8	7/8x14	-10	5/8	-10	2.43	62	1	0.98	25
30682-10-10C~	5/8	7/8x14	-10	5/8	-10	2.43	62	1	0.98	25
30682-12-8+	3/4	1-1/16x12	-12	1/2	-8	2.25	57	1-1/4	1.20	30
30682-12-8B+	3/4	1-1/16x12	-12	1/2	-8	2.25	57	1-1/4	1.20	30
30682-12-12	3/4	1-1/16x12	-12	3/4	-12	2.65	67	1-1/4	1.20	30
30682-12-12B	3/4	1-1/16x12	-12	3/4	-12	2.65	67	1-1/4	1.20	30
30682-12-12C	3/4	1-1/16x12	-12	3/4	-12	2.65	67	1-1/4	1.20	30
30682-14-12+	7/8	1-3/16x12	-14	3/4	-12	2.69	68	1-3/8	1.24	31
30682-16-12B+	1	1-5/16X12	-16	3/4	-12	2.78	71	1-3/8	1.33	34
30682-16-16+	1	1-5/16X12	-16	1	-16	2.77	70	1-3/8	1.32	34
30682-16-16B	1	1-5/16X12	-16	1	-16	2.77	70	1-3/8	1.32	34

+ Non-Standard

82 Series Fittings


Use with 801, 804, 821, 821FR, 831 and 836 hoses.

JIC

33782 Female JIC 37° - Swivel 45° Elbow - Short Drop

~ These 33782 fittings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations. The -6 and -12 SAE (45°) swivel fittings are shown under part number 37782.

Note: "C" - Stainless Steel Fitting.




# Part Number	 Thread			 Hose		A		E		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	inch	inch	mm
33782-4-4~	1/4	7/16x20	-4	1/4	-4	1.79	45	0.33	8	7/16	9/16	1.04	26
33782-6-6	3/8	9/16x18	-6	3/8	-6	2.10	53	0.39	10	1/2	11/16	1.20	30
33782-8-8~	1/2	3/4x16	-8	1/2	-8	2.58	66	0.55	14	5/8	7/8	1.53	39
33782-8-8C~+	1/2	3/4x16	-8	1/2	-8	2.56	65	0.55	14	5/8	7/8	1.51	38
33782-10-8~+	5/8	7/8x14	-10	1/2	-8	2.63	67	0.65	17	3/4	1	1.58	40
33782-10-10~+	5/8	7/8x14	-10	5/8	-10	3.04	77	0.64	16	3/4	1	1.59	40
33782-12-12+	3/4	1-1/16x12	-12	3/4	-12	3.36	85	0.78	20	7/8	1-1/4	1.91	49

33982 Female JIC 37° - Swivel 90° Elbow - Short Drop

~ These 33982 fittings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations. The -6 and -12 SAE (45°) swivel fittings are shown under part number 37982.


Note: "C" - Stainless Steel Fitting.



# Part Number	 Thread			 Hose		A		E		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	inch	inch	mm
33982-4-4~	1/4	7/16x20	-4	1/4	-4	1.60	41	0.83	21	7/16	9/16	0.85	22
33982-5-4~+	5/16	1/2x20	-5	1/4	-4	1.88	48	0.77	20	7/16	9/16	1.13	29
33982-6-4+	3/8	9/16x18	-6	1/4	-4	1.84	47	0.85	22	1/2	11/16	1.08	27
33982-6-6	3/8	9/16x18	-6	3/8	-6	1.96	50	0.85	22	1/2	11/16	1.09	28
33982-8-6~+	1/2	3/4x16	-8	3/8	-6	2.18	55	1.09	28	5/8	7/8	1.27	32
33982-8-8~	1/2	3/4x16	-8	1/2	-8	2.33	59	1.09	28	5/8	7/8	1.29	33
33982-8-8C~+	1/2	3/4x16	-8	1/2	-8	2.33	59	1.09	28	5/8	7/8	1.29	33
33982-10-8~+	5/8	7/8x14	-10	1/2	-8	2.48	63	1.24	31	3/4	1	1.43	36
33982-10-10~+	5/8	7/8x14	-10	5/8	-10	2.90	74	1.23	31	3/4	1	1.45	37
33982-12-10+	3/4	1-1/16x12	-12	5/8	-10	3.26	83	1.81	46	7/8	1-1/4	1.81	46
33982-12-12	3/4	1-1/16x12	-12	3/4	-12	3.29	84	1.82	46	7/8	1-1/4	1.83	46
33982-14-12+	7/8	1-3/16x12	-14	3/4	-12	3.26	83	1.91	49	7/8	1-3/8	1.81	46

+ Non-Standard


34182 Female JIC 37° - Swivel 90° Elbow - Long Drop



~ These 34182 fittings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations.

Part Number	Thread			Hose		A		E		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	inch	inch	mm
34182-4-4~	1/4	7/16x20	-4	1/4	-4	1.54	39	1.80	46	7/16	9/16	0.78	20
34182-6-6	3/8	9/16x18	-6	3/8	-6	1.97	50	2.18	55	1/2	11/16	1.08	27

30482 Male SAE 45° - Rigid Straight



Note: "B" - Brass Fitting.

Part Number	Thread			Hose		A		H	B	
	inch			inch		inch	mm	inch	inch	mm
30482-4-4+	1/4	7/16x20	-4	1/4	-4	1.51	38	7/16	0.76	19
30482-4-4B	1/4	7/16x20	-4	1/4	-4	1.51	38	7/16	0.76	19
30482-4-6B+	1/4	7/16x20	-4	3/8	-6	1.78	45	1/2	0.89	23
30482-5-4+	5/16	1/2x20	-5	1/4	-4	1.61	41	9/16	0.85	22
30482-5-4B	5/16	1/2x20	-5	1/4	-4	1.61	41	9/16	0.85	22
30482-5-6+	5/16	1/2x20	-5	3/8	-6	1.84	47	1/2	0.95	24
30482-5-6B+	5/16	1/2x20	-5	3/8	-6	1.84	47	1/2	0.95	24
30482-6-6+	3/8	5/8x18	-6	3/8	-6	1.84	47	5/8	0.94	24
30482-6-6B	3/8	5/8x18	-6	3/8	-6	1.84	47	5/8	0.94	24
30482-8-8+	1/2	3/4x16	-8	1/2	-8	2.15	55	3/4	1.10	28
30482-8-8B	1/2	3/4x16	-8	1/2	-8	2.15	55	3/4	1.10	28
30482-10-10+	5/8	7/8x14	-10	5/8	-10	2.70	69	7/8	1.25	32
30482-12-12+	3/4	1-1/16x14	-12	3/4	-12	2.86	73	1-1/16	1.41	36

+ Non-Standard


Use with 801, 804, 821, 821FR, 831 and 836 hoses.

30882 Female SAE 45° - Swivel Straight

~ These 30882 fittings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations. The -6 and -12 JIC (37°) swivel fittings are shown under part number 30682.


Note: "B" - Brass Fitting.

Note: Notch in nut for SAE 45° flare.



Part Number	Thread			Hose		A		W	B	
	inch			inch		inch	mm	inch	inch	mm
30882-4-4~	1/4	7/16x20	-4	1/4	-4	1.52	39	9/16	0.76	19
30882-4-4B~	1/4	7/16x20	-4	1/4	-4	1.52	39	9/16	0.76	19
30882-5-4~	5/16	1/2x20	-5	1/4	-4	1.58	40	5/8	0.83	21
30882-5-4B~	5/16	1/2x20	-5	1/4	-4	1.58	40	5/8	0.83	21
30882-5-4C~+	5/16	1/2x20	-5	1/4	-4	1.58	40	5/8	0.83	21
30882-6-4+	3/8	5/8x18	-6	1/4	-4	1.67	42	3/4	0.92	23
30882-6-6	3/8	5/8x18	-6	3/8	-6	1.81	46	3/4	0.90	23
30882-6-6B	3/8	5/8x18	-6	3/8	-6	1.81	46	3/4	0.90	23
30882-6-8+	3/8	5/8x18	-6	1/2	-8	1.96	50	3/4	0.90	23
30882-8-6~+	1/2	3/4x16	-8	3/8	-6	1.86	47	7/8	0.96	24
30882-8-6B~	1/2	3/4x16	-8	3/8	-6	1.86	47	7/8	0.96	24
30882-8-6C~+	1/2	3/4x16	-8	3/8	-6	1.86	47	7/8	0.96	24
30882-8-8~	1/2	3/4x16	-8	1/2	-8	2.01	51	7/8	0.98	25
30882-8-8B~	1/2	3/4x16	-8	1/2	-8	2.01	51	7/8	0.98	25
30882-10-8B~	5/8	7/8x14	-10	1/2	-8	2.14	54	1	1.09	28
30882-10-10~	5/8	7/8x14	-10	5/8	-10	2.54	65	1	1.09	28
30882-10-10B~	5/8	7/8x14	-10	5/8	-10	2.54	65	1	1.09	28
30882-12-12	3/4	1-1/16x14	-12	3/4	-12	2.65	67	1-1/4	1.19	30
30882-12-12B	3/4	1-1/16x14	-12	3/4	-12	2.65	67	1-1/4	1.19	30

37782 Female SAE 45° Swivel - 45° Elbow




Note: Notch in nut for SAE 45° flare.

Part Number	Thread			Hose		A		E		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	inch	inch	mm
37782-4-4	1/4	7/16x20	-4	1/4	-4	1.79	45	0.33	8	7/16	9/16	1.04	26
37782-6-6	3/8	5/8x18	-6	3/8	-6	2.08	53	0.39	10	1/2	3/4	1.18	30
37782-8-8	1/2	3/4x16	-8	1/2	-8	2.58	66	0.55	14	5/8	7/8	1.53	39

+ Non-Standard


37982 Female SAE 45° Swivel - 90° Elbow



Note: Notch in nut for SAE 45° flare.

 Part Number	 Thread			 Hose		A		E		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	mm	inch	mm
37982-4-4	1/4	7/16x20	-4	1/4	-4	1.60	41	0.83	21	7/16	9/16	0.85	22
37982-6-6	3/8	5/8x18	-6	3/8	-6	1.98	50	0.85	22	1/2	3/4	1.08	27
37982-8-8	1/2	3/4x16	-8	1/2	-8	2.33	59	1.09	28	5/8	7/8	1.28	33

32882 Male Inverted SAE 45° - Swivel Straight




 Part Number	 Thread			 Hose		A		H	W	B	
	inch			inch		inch	mm	inch	inch	inch	mm
32882-3-4	3/16	3/8x24	-3	1/4	-4	2.17	55	3/8	3/8	1.41	36
32882-4-4	1/4	7/16x24	-4	1/4	-4	2.16	55	7/16	7/16	1.40	36
32882-5-4	5/16	1/2x20	-5	1/4	-4	2.24	57	7/16	1/2	1.56	40
32882-5-6+	5/16	1/2x20	-5	3/8	-6	2.39	61	1/2	1/2	1.56	40
32882-6-6	3/8	5/8x18	-6	3/8	-6	2.58	66	1/2	5/8	1.68	43
32882-8-8	1/2	3/4x18	-8	1/2	-8	2.82	72	5/8	3/4	1.78	45
32882-10-10	5/8	7/8x18	-10	5/8	-10	3.37	86	3/4	7/8	1.92	49
32882-12-12+	3/4	1-1/16x16	-12	3/4	-12	2.87	73	7/8	1-1/16	1.42	36

+ Non-Standard

Use with 801, 804, 821, 821FR, 831 and 836 hoses.


36782 Male Inverted SAE 45° - Swivel 45° Elbow



Note: "C" - Stainless Steel Fitting.

Part Number	Thread			Hose		A		E		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	inch	inch	mm
36782-4-4	1/4	7/16x24	-4	1/4	-4	1.85	47	0.62	16	7/16	7/16	1.10	28
36782-6-6	3/8	5/8x18	-6	3/8	-6	2.64	67	0.94	24	1/2	5/8	1.75	44
36782-6-6C+	3/8	5/8x18	-6	3/8	-6	2.64	67	0.94	24	1/2	5/8	1.75	44

36982 Male Inverted SAE 45° - Swivel 90° Elbow



Part Number	Thread			Hose		A		E		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	inch	inch	mm
36982-4-4	1/4	7/16x24	-4	1/4	-4	1.92	49	1.56	40	3/8	7/16	1.25	32
36982-5-4	5/16	1/2x20	-5	1/4	-4	2.13	54	1.65	42	7/16	1/2	1.38	35
36982-6-6	3/8	5/8x18	-6	3/8	-6	2.30	58	1.69	43	1/2	5/8	1.41	36
36982-6-10+	3/8	5/8x18	-6	5/8	-10	4.37	111	1.69	43	3/4	5/8	1.43	36
36982-8-8+	1/2	3/4x18	-8	1/2	-8	2.53	64	1.88	48	5/8	3/4	1.49	38


+ Non-Standard

82 Series Fittings


Inverted SAE

Use with 801, 804, 821, 821FR, 831 and 836 hoses.

32982 Female Inverted SAE 45° - Rigid Straight



Note: "B" - Brass Fitting.

# Part Number	 Thread			 Hose		A		 H	B	
	inch			inch		inch	mm	inch	inch	mm
32982-3-4B	3/16	3/8x24	-3	1/4	-4	1.19	30	7/16	0.43	11
32982-4-4B	1/4	7/16x24	-4	1/4	-4	1.19	30	1/2	0.43	11
32982-5-4B	5/16	1/2x20	-5	1/4	-4	1.25	32	9/16	0.45	11
32982-5-6B+	5/16	1/2x20	-5	3/8	-6	1.20	30	9/16	0.50	13
32982-6-6B	3/8	5/8x18	-6	3/8	-6	1.44	37	3/4	0.54	14
32982-8-6B+	1/2	3/4x18	-8	3/8	-6	1.47	37	7/8	0.57	14
32982-8-8B	1/2	3/4x18	-8	1/2	-8	1.63	41	7/8	0.57	14
32982-12-12B+	3/4	1-1/6x16	-12	3/4	-12	2.13	54	1-1/4	0.68	17

+ Non-Standard

Use with 801, 804, 821, 821FR, 831 and 836 hoses.


3J082 Male Seal-Lok® - Rigid Straight (with O-Ring)

Note: Seal-Lok® torque table in Section G.

Note: O-Rings are listed in Section F.

Note: Fittings with a "SM" suffix have a metric hex.

Note: Part number 3JM82 is 3J082 without Nitrile O-Ring.



Part Number	Thread			Hose		A		H	B	
	inch			inch		inch	mm	inch	inch	mm
3J082-6-6-SM	3/8	11/16x16	-6	3/8	-6	1.74	44	19mm	0.85	22
3J082-8-8	1/2	13/16x16	-8	1/2	-8	1.90	48	9/16	0.86	22
3J082-8-8-SM	1/2	13/16x16	-8	1/2	-8	1.90	48	22mm	0.86	22
3J082-8-10-SM+	1/2	13/16x16	-8	5/8	-10	2.30	58	22mm	0.86	22
3J082-10-8-SM+	5/8	1x14	-10	1/2	-8	2.17	55	27mm	1.07	27
3J082-10-10-SM	5/8	1x14	-10	5/8	-10	2.57	65	27mm	1.12	28
3J082-12-12+	3/4	1-3/16x12	-12	3/4	-12	2.68	68	1-1/8	1.24	31
3J082-12-12-SM+	3/4	1-3/16x12	-12	3/4	-12	2.68	68	32mm	1.24	31


3JC82 Female Seal-Lok® - Swivel Straight - Short

Note: Seal-Lok® torque table in Section G.

Note: O-Rings are listed in Section F.

Note: Fittings with a "SM" suffix have a metric hex.

Note: When measuring overall length to end of nut, B + C must be used to calculate cut-off allowance.




Part Number	Thread			Hose		A		C		H	W	B	
	inch			inch		inch	mm	inch	mm	inch	inch	inch	mm
3JC82-4-4	1/4	9/16x18	-4	1/4	-4	1.40	36	0.32	8	9/16	11/16	0.65	17
3JC82-4-4C	1/4	9/16x18	-4	1/4	-4	1.40	36	0.32	8	9/16	11/16	0.65	17
3JC82-4-4-SM+	1/4	9/16x18	-4	1/4	-4	1.40	36	0.32	8	17mm	17mm	0.66	17
3JC82-6-6	3/8	11/16x16	-6	3/8	-6	1.59	40	0.38	10	11/16	13/16	0.69	18
3JC82-6-6C	3/8	11/16x16	-6	3/8	-6	1.59	40	0.38	10	11/16	13/16	0.69	18
3JC82-6-6-SM	3/8	11/16x16	-6	3/8	-6	1.59	40	0.38	10	19mm	22mm	0.70	18
3JC82-8-6	1/2	13/16x16	-8	3/8	-6	1.65	42	0.38	10	13/16	15/16	0.76	19
3JC82-8-6-SM+	1/2	13/16x16	-8	3/8	-6	1.70	43	0.43	11	22mm	24mm	0.80	20
3JC82-8-8	1/2	13/16x16	-8	1/2	-8	1.80	46	0.43	11	13/16	15/16	0.75	19
3JC82-8-8C	1/2	13/16x16	-8	1/2	-8	1.80	46	0.43	11	13/16	15/16	0.75	19
3JC82-8-8-SM	1/2	13/16x16	-8	1/2	-8	1.80	46	0.43	11	22mm	24mm	0.76	19
3JC82-8-10+	1/2	13/16x16	-8	5/8	-10	2.25	57	0.43	11	3/4	15/16	0.81	21
3JC82-8-10-SM	1/2	13/16x16	-8	5/8	-10	2.25	57	0.43	11	22mm	24mm	0.81	21
3JC82-10-8-SM	5/8	1x14	-10	1/2	-8	2.00	51	0.43	11	24mm	30mm	0.95	24
3JC82-10-10	5/8	1x14	-10	5/8	-10	2.40	61	0.53	13	15/16	1-1/8	0.96	24
3JC82-10-10B+	5/8	1x14	-10	5/8	-10	2.40	61	0.53	13	15/16	1-1/8	0.96	24
3JC82-10-10C+	5/8	1x14	-10	5/8	-10	2.40	61	0.53	13	15/16	1-1/8	0.95	24
3JC82-10-10-SM	5/8	1x14	-10	5/8	-10	2.40	61	0.43	11	24mm	30mm	0.95	24
3JC82-10-12+	5/8	1x14	-10	3/4	-12	2.40	61	0.53	13	1	1-1/8	0.96	24
3JC82-12-12	3/4	1-3/16x12	-12	3/4	-12	2.63	67	0.57	14	1-1/8	1-3/8	1.18	30
3JC82-12-12C	3/4	1-3/16x12	-12	3/4	-12	2.63	67	0.57	14	1-1/8	1-3/8	1.18	30
3JC82-12-12-SM+	3/4	1-3/16x12	-12	3/4	-12	2.63	67	0.57	14	32mm	36mm	1.19	30
3JC82-16-16+	1	1-7/16x12	-16	1	-16	2.61	66	0.58	15	1-3/8	1-5/8	1.16	29
3JC82-16-16B	1	1-7/16x12	-16	1	-16	2.61	66	0.58	15	1-3/8	1-5/8	1.16	29

+ Non-Standard

Use with 801, 804, 821, 821FR, 831 and 836 hoses.


3J782 Female Seal-Lok® - Swivel 45° Elbow



Note: Seal-Lok® torque table in Section G.
 Note: "C" - Stainless Steel Fitting.
 Note: O-Rings are listed in Section F.
 Note: Fittings with a "SM" suffix have a metric hex.

Part Number						A		E		W	B	
	Thread			Hose								
	inch	inch		inch		inch	mm	inch	mm	inch	inch	mm
3J782-4-4	1/4	9/16x18	-4	1/4	-4	1.74	44	0.39	10	11/16	0.99	25
3J782-4-4C+	1/4	9/16x18	-4	1/4	-4	1.94	49	0.41	10	11/16	1.19	30
3J782-4-4-SM+	1/4	9/16x18	-4	1/4	-4	1.74	44	0.39	10	17mm	0.99	25
3J782-6-6	3/8	11/16x16	-6	3/8	-6	1.99	51	0.43	11	13/16	1.09	28
3J782-6-6-SM+	3/8	11/16x16	-6	3/8	-6	1.99	51	0.43	11	22mm	1.09	28
3J782-8-6+	1/2	13/16x16	-8	3/8	-6	2.19	56	0.59	15	15/16	1.29	33
3J782-8-8	1/2	13/16x16	-8	1/2	-8	2.41	61	0.59	15	15/16	1.36	35
3J782-8-8-SM	1/2	13/16x16	-8	1/2	-8	2.41	61	0.59	15	24mm	1.36	35
3J782-10-10	5/8	1x14	-10	5/8	-10	2.95	75	0.63	16	1-1/8	1.50	38
3J782-10-10-SM+	5/8	1x14	-10	5/8	-10	2.95	75	0.63	16	30mm	1.50	38
3J782-12-12	3/4	1-3/16x12	-12	3/4	-12	3.42	87	0.83	21	1-3/8	1.97	50
3J782-12-12-SM+	3/4	1-3/16x12	-12	3/4	-12	3.42	87	0.83	21	36mm	1.97	50

3J982 Female Seal-Lok® - Swivel 90° Elbow - Short Drop




Note: Seal-Lok® torque table in Section G.
 Note: O-Rings are listed in Section F.
 Note: Fittings with "SM" suffix have metric hex.

Part Number						A		E		W	B	
	Thread			Hose								
	inch	inch		inch		inch	mm	inch	mm	inch	inch	mm
3J982-4-4	1/4	9/16x18	-4	1/4	-4	1.55	39	0.83	21	11/16	0.80	20
3J982-4-4-SM+	1/4	9/16x18	-4	1/4	-4	1.55	39	0.83	21	17mm	0.80	20
3J982-6-6	3/8	11/16x16	-6	3/8	-6	1.85	47	0.91	23	13/16	0.95	24
3J982-6-6-SM	3/8	11/16x16	-6	3/8	-6	1.85	47	0.91	23	22mm	0.95	24
3J982-6-8	3/8	11/16x16	-6	1/2	-8	2.09	53	0.91	23	13/16	1.04	26
3J982-8-6	1/2	13/16x16	-8	3/8	-6	1.94	49	1.14	29	15/16	1.04	26
3J982-8-8	1/2	13/16x16	-8	1/2	-8	2.16	55	1.14	29	15/16	1.11	28
3J982-8-8-SM	1/2	13/16x16	-8	1/2	-8	2.16	55	1.14	29	24mm	1.11	28
3J982-8-10-SM	1/2	13/16x16	-8	5/8	-10	2.74	70	1.15	29	24mm	1.29	33
3J982-10-10	5/8	1x14	-10	5/8	-10	2.76	70	1.26	32	1-1/8	1.31	33
3J982-10-10-SM	5/8	1x14	-10	5/8	-10	2.76	70	1.26	32	36mm	1.31	33
3J982-12-12	3/4	1-3/16x12	-12	3/4	-12	3.27	83	1.89	48	1-3/8	1.82	46

+ Non-Standard


3J582 Female Seal-Lok® - Swivel 90° Elbow - Medium Drop



Note: Seal-Lok® torque table in Section G.
 Note: O-Rings are listed in Section F.
 Note: Fittings with "SM" suffix have metric hex.

Part Number	Thread			Hose		A		E		W	B	
	inch	inch	inch	inch	inch	inch	mm	inch	mm	inch	inch	mm
3J582-10-10+	5/8	1x14	-10	5/8	-10	2.76	70	1.85	47	1-1/8	1.31	33
3J582-10-10-SM	5/8	1x14	-10	5/8	-10	2.76	70	1.85	47	30mm	1.31	33

3J182 Female Seal-Lok® - Swivel 90° Elbow - Long Drop




Note: Seal-Lok® torque table in Section G.
 Note: O-Rings are listed in Section F.
 Note: Fittings with "SM" suffix have metric hex.

Part Number	Thread			Hose		A		E		W	B	
	inch	inch	inch	inch	inch	inch	mm	inch	mm	inch	inch	mm
3J182-4-4	1/4	9/16x18	-4	1/4	-4	1.55	39	1.81	46	11/16	0.80	20
3J182-4-4-SM+	1/4	9/16x18	-4	1/4	-4	1.55	39	1.81	46	17mm	0.80	20
3J182-6-6	3/8	11/16x16	-6	3/8	-6	1.85	47	2.13	54	13/16	0.95	24
3J182-6-6-SM+	3/8	11/16x16	-6	3/8	-6	1.85	47	2.13	54	22mm	0.95	24
3J182-8-6-SM+	1/2	13/16x16	-6	3/8	-6	2.01	51	2.52	64	24mm	1.11	28
3J182-8-8	1/2	13/16x16	-8	1/2	-8	2.16	55	2.52	64	15/16	1.11	28
3J182-8-8-SM	1/2	13/16x16	-8	1/2	-8	2.16	55	2.52	64	24mm	1.11	28
3J182-10-10+	5/8	1x14	-10	5/8	-10	2.76	70	2.76	70	1-1/8	1.31	33
3J182-10-10-SM+	5/8	1x14	-10	5/8	-10	2.76	70	2.76	70	30mm	1.31	33

+ Non-Standard


Use with 801, 804, 821, 821FR, 831 and 836 hoses.

33482 Male Standpipe - Rigid Straight (Inch Size Tube O.D.)




Note: "B" - Brass Fitting.

Note: "C" - Stainless Steel Fitting.

 Part Number	 Thread		 Hose		A		D		B	
	inch		inch		inch	mm	inch	mm	inch	mm
33482-3-4B	3/16	-3	1/4	-4	1.63	41	0.75	19	0.87	22
33482-4-4B	1/4	-4	1/4	-4	1.89	48	1.02	26	1.13	29
33482-4-4C	1/4	-4	1/4	-4	1.89	48	1.02	26	1.13	29
33482-5-4B	5/16	-5	1/4	-4	1.95	50	1.08	27	1.19	30
33482-5-8B+	5/16	-5	1/4	-8	2.27	58	2.27	58	1.22	31
33482-6-4+	3/8	-6	1/4	-4	2.09	53	1.22	31	1.34	34
33482-6-6B	3/8	-6	3/8	-6	2.23	57	1.22	31	1.33	34
33482-6-6C	3/8	-6	3/8	-6	2.23	57	1.22	31	1.33	34
33482-8-8B	1/2	-8	1/2	-8	2.16	55	0.97	25	1.10	28
33482-8-8C	1/2	-8	1/2	-8	2.16	55	0.97	25	1.10	28
33482-10-10B	5/8	-10	5/8	-10	2.63	67	1.00	25	1.17	30
33482-10-10C+	5/8	-10	5/8	-10	2.63	67	1.00	25	1.17	30
33482-12-12B+	3/4	-12	3/4	-12	2.63	67	1.00	25	1.17	30
33482-12-12C+	3/4	-12	3/4	-12	2.63	67	1.00	25	1.18	30

38282 Push-Lok Union



Note: "B" - Brass Fitting.

Note: "C" - Stainless Steel Fitting.

 Part Number	 Hose		A	
	inch		inch	mm
38282-4-4+	1/4	-4	1.80	46
38282-4-4B	1/4	-4	1.80	46
38282-4-4C+	1/4	-4	1.80	46
38282-6-6+	3/8	-6	2.15	55
38282-6-6B	3/8	-6	2.15	55
38282-6-6C+	3/8	-6	2.15	55
38282-8-8	1/2	-8	2.51	64
38282-8-8B	1/2	-8	2.51	64
38282-8-8C+	1/2	-8	2.51	64
38282-10-10	5/8	-10	3.31	84
38282-10-10B+	5/8	-10	3.31	84
38282-12-12	3/4	-12	3.31	84
38282-12-12B+	3/4	-12	3.31	84


+ Non-Standard

82 Series Fittings

Metric L

Use with 801, 804, 821, 821FR, 831 and 836 hoses.

3D082 Male Metric L – Rigid Straight (24° Cone)




Note: Fittings with an "SA" suffix have an inch hex

Note: Mates with EO "L" Series Fittings.

Note: "C" - Stainless Steel Fitting.

Part Number	Thread			Hose		A		H	B	
	inch			inch		inch	mm	inch	inch	mm
3D082-6-4	6	M12x1,5	-6	1/4	-4	1.34	34	12	0.55	14
3D082-6-6-SA+	6	M12x1,5	-6	3/8	-6	1.59	40	5/8	0.69	18
3D082-8-4	8	M14x1,5	-8	1/4	-4	1.38	35	14	0.59	15
3D082-10-6	10	M16x1,5	-10	3/8	-6	1.57	40	17	0.63	16
3D082-12-6	12	M18x1,5	-12	3/8	-6	1.61	41	19	0.67	17
3D082-15-8	15	M22x1,5	-15	1/2	-8	1.77	45	22	0.71	18
3D082-18-10	18	M26x1,5	-18	5/8	-10	2.28	58	37	0.79	20
3D082-22-12	22	M30x2	-22	3/4	-12	2.32	59	32	0.83	21

31D82 Male Standpipe Metric L - Rigid Straight



Note: Mates with EO "L" Series Fittings.

Part Number	Thread		Hose		A		D		B	
	mm		inch		inch	mm	inch	mm	inch	mm
31D82-6-4	6	-6	1/4	-4	1.73	44	0.87	22	0.98	25
31D82-8-4	8	-8	1/4	-4	1.73	44	0.87	22	0.98	25
31D82-10-6	10	-10	3/8	-6	1.93	49	0.91	23	1.02	26
31D82-12-6	12	-12	3/8	-6	1.93	49	0.91	23	1.06	27
31D82-15-8	15	-15	1/2	-8	2.17	55	0.98	25	1.10	28
31D82-18-10	18	-18	5/8	-10	2.64	67	1.02	26	1.10	28
31D82-22-12	22	-22	3/4	-12	2.72	69	1.10	28	1.22	31

+ Non-Standard


Use with 801, 804, 821, 821FR, 831 and 836 hoses.

3C382 Female Metric L - Swivel Straight (Ball Nose)

Note: Mates with EO "L" Series Fittings.

Note: When measuring overall length to end of nut, B + C must be used to calculate cut-off allowance.

Note: "C" - Stainless Steel Fitting.




Part Number	Thread			Hose		A		C		W	B	
	mm			inch		inch	mm	inch	mm	mm	inch	mm
3C382-6-4	6	M12x1,5	-6	1/4	-4	1.38	35	0.09	2	14	0.55	14
3C382-8-4	8	M14x1,5	-8	1/4	-4	1.38	35	0.11	3	17	0.55	14
3C382-10-6	10	M16x1,5	-10	3/8	-6	1.50	38	0.06	1	19	0.55	14
3C382-12-6	12	M18x1,5	-12	3/8	-6	1.54	39	0.10	2	22	0.55	14
3C382-15-8	15	M22x1,5	-15	1/2	-8	1.77	45	0.17	4	27	0.63	16
3C382-18-10	18	M26x1,5	-18	5/8	-10	1.67	42	0.10	2	32	0.63	16
3C382-22-12	22	M30x2	-22	3/4	-12	2.24	57	0.18	4	36	0.63	16

3C482 Female Metric L - Swivel 45° Elbow (Ball Nose)

Note: Mates with EO "L" Series Fittings.

Note: "C" - Stainless Steel Fitting.



Part Number	Thread			Hose		A		E		W	B	
	mm			inch		inch	mm	inch	mm	mm	inch	mm
3C482-6-4	6	M12x1,5	-6	1/4	-4	2.13	54	0.59	15	14	1.30	33
3C482-8-4	8	M14x1,5	-8	1/4	-4	2.13	54	0.63	16	19	1.34	34
3C482-10-6	10	M16x1,5	-10	3/8	-6	2.36	60	0.67	17	19	1.42	36
3C482-12-6	12	M18x1,5	-12	3/8	-6	2.40	61	0.71	18	22	1.46	37
3C482-15-8	15	M22x1,5	-15	1/2	-8	2.95	75	0.79	20	27	1.85	47
3C482-18-10	18	M26x1,5	-18	5/8	-10	3.82	97	1.14	29	32	2.32	59
3C482-22-12	22	M30x2	-22	3/4	-12	3.58	91	0.91	23	36	2.09	53


+ Non-Standard

82 Series Fittings

Metric L / BSP

Use with 801, 804, 821, 821FR, 831 and 836 hoses.

3C582 Female Metric L - Swivel 90° Elbow (Ball Nose)




Note: Mates with EO "L" Series Fittings.

Note: "C" - Stainless Steel Fitting.

Part Number	Thread			Hose		A		E		W	B	
	mm	mm	mm	inch	inch	inch	mm	inch	mm	mm	inch	mm
3C582-6-4	6	M12x1,5	-6	1/4	-4	1.69	43	1.02	26	14	0.87	22
3C582-8-4	8	M14x1,5	-8	1/4	-4	1.77	45	1.10	28	19	0.94	24
3C582-10-6	10	M16x1,5	-10	3/8	-6	2.01	51	1.18	30	19	1.02	26
3C582-12-6	12	M18x1,5	-12	3/8	-6	2.01	51	1.22	31	22	1.02	26
3C582-15-8	15	M22x1,5	-15	1/2	-8	2.56	65	1.57	40	27	1.46	37
3C582-18-10	18	M26x1,5	-18	5/8	-10	3.39	86	2.32	59	32	1.89	48
3C582-22-12	22	M30x2	-22	3/4	-12	3.39	86	1.97	50	36	1.89	48

39182 Male BSP Taper Pipe - Rigid Straight



Note: Fittings with an "SA" suffix have an inch hex

Note: "B" - Brass Fitting.

Note: "C" - Stainless Steel Fitting.

Part Number	Thread		Hose		A		H	B	
	inch	inch	inch	inch	inch	mm	mm	inch	mm
39182-4-4	1/4x19	-4	1/4	-4	1.65	42	14	0.83	21
39182-4-4B	1/4x19	-4	1/4	-4	1.65	42	14	0.83	21
39182-4-4C+	1/4x19	-4	1/4	-4	1.65	42	14	0.83	21
39182-4-6B	1/4x19	-4	3/8	-6	1.83	46	19	0.94	24
39182-6-6	3/8x19	-6	3/8	-6	1.89	48	19	0.98	25
39182-6-6B	3/8x19	-6	3/8	-6	1.89	48	19	0.98	25
39182-6-6C-SA+	3/8x19	-6	3/8	-6	1.84	47	7/8"	0.94	24
39182-6-8B	3/8x19	-6	1/2	-8	1.93	49	19	0.98	25
39182-8-8	1/2x14	-8	1/2	-8	2.20	56	22	1.10	28
39182-8-8B	1/2x14	-8	1/2	-8	2.20	56	22	1.10	28
39182-8-8C+	1/2x14	-8	1/2	-8	2.20	56	22	1.10	28
39182-12-10B	3/4x14	-12	5/8	-10	2.64	67	27	1.14	29
39182-12-12	3/4x14	-12	3/4	-12	2.72	69	27	1.22	31
39182-12-12B	3/4x14	-12	3/4	-12	2.72	69	27	1.22	31
39182-12-12C-SA+	3/4x14	-12	3/4	-12	2.70	69	1-3/8"	1.22	31


+ Non-Standard

82 Series Fittings

BSP

Use with 801, 804, 821, 821FR, 831 and 836 hoses.

39282 Female BSP Parallel Pipe Swivel - Straight (60° Cone)




Note: When measuring overall length to end of nut, B + C must be used to calculate cut-off allowance.

Note: "B" - Brass Fitting.

Part Number	Thread		Hose		A		C		W	B	
	mm		inch		inch	mm	inch	mm	mm	inch	mm
39282-4-4	1/4x19	-4	1/4	-4	1.34	34	0.22	6	17	0.55	14
39282-4-4B+	1/4x19	-4	1/4	-4	1.60	41	0.22	6	19	0.85	22
39282-6-6	3/8x19	-6	3/8	-6	1.50	38	0.26	7	19	0.55	14
39282-6-6B	3/8x19	-6	3/8	-6	1.50	38	0.26	7	19	0.55	14
39282-8-8	1/2x14	-8	1/2	-8	1.77	45	0.28	7	27	1.06	27
39282-10-10+	5/8x14	-10	5/8	-10	2.44	62	0.37	9	30	1.18	30
39282-12-12	3/4x14	-12	3/4	-12	2.13	54	0.35	9	36	1.42	36

3D982 Male BSP Parallel Pipe - Rigid Straight (60° Cone)



Note: When used in a part, a bonded seal must be used.

Note: "C" - Stainless Steel Fitting.

Part Number	Thread		Hose		A		H	B	
	inch		inch		inch	mm	mm	inch	mm
3D982-2-4	1/8x28	-2	1/4	-4	1.42	36	14	0.63	16
3D982-4-4	1/4x19	-4	1/4	-4	1.61	41	19	0.83	21
3D982-4-6	1/4x19	-4	3/8	-6	1.77	45	19	0.83	21
3D982-6-6	3/8x19	-6	3/8	-6	1.77	45	22	0.87	22
3D982-8-8	1/2x14	-8	1/2	-8	2.09	53	27	0.98	25
3D982-8-8C+	1/2x14	-8	1/2	-8	2.09	53	27	0.98	25
3D982-8-10	1/2x14	-8	5/8	-10	2.44	62	27	0.94	24
3D982-10-10	5/8x14	-10	5/8	-10	2.52	64	30	1.06	27
3D982-12-12	3/4x14	-12	3/4	-12	2.56	65	32	1.06	27

+ Non-Standard

以上内容仅为本文档的试下载部分，为可阅读页数的一半内容。如要下载或阅读全文，请访问：<https://d.book118.com/597035013000010056>